

SINGLE-ACTING CYLINDERS

MODEL NUMBER	CAPACITY (TONS)	STROKE (Inches)	OIL CAP (Cu. In.)	CYLINDER BORE DIA. (Inches)	CYLINDER EFFECTIVE AREA(Sq.In.)	RETURN SPRING	HEIGHT		OUTSIDE DIA.		THREAD SIZE			WEIGHT (Lbs.)
							Min.	Max.	Piston	Cylinder	Piston (NPT)	CYL. COLLAR (Inches x Thrd.)	INTERNAL BASE (NPT)	
910026A	10	6.125	13.67	1.69	2.23	YES	12.5"	18.625"	1.5"	2.25"	1.25 x 11.5	2.25 x 14	1.25 x 11.5	10
910027A	10	2.125	4.75	1.69	2.23	YES	4.5"	6.625"	1.5"	2.25"	---	2.25 x 14	---	6
910029A	10	10.125	22.59	1.69	2.23	YES	16.5"	26.625"	1.5"	2.25"	1.25 x 11.5	2.25 x 14	1.25 x 11.5	14
910030	10	12	26.76	1.69	2.23	YES	15.75"	27.75"	1.5"	2.25"	---	2.25 x 14	---	16.5
910047	10	14	31.22	1.69	2.23	YES	17.75"	31.75"	1.5"	2.25"	---	2.25 x 14	---	18
915006	15	6	18.84	2.00	3.14	YES	10.6875"	16.6875"	1.63"	2.75"	---	2.75 x 16	---	15
925026B	20	1.75	7.77	2.38	4.44	YES	3.875"	5.625"	2.00"	3.63"	---	---	---	11
925023	25	4	20.60	2.56	5.15	YES	8.5"	12.5"	2.25"	3.38"	---	3.3125 x 12	---	18
925024	25	10.25	52.79	2.56	5.15	YES	14.75"	25"	2.25"	3.38"	---	3.3125 x 12	---	31
925025A	25	6.25	32.19	2.56	5.15	YES	14.875"	21.125"	2.25"	3.38"	2 x 11.5	3.3125 x 12	2 x 11.5	22
925027A	25	14.25	73.39	2.56	5.15	YES	22.875"	37.125"	2.25"	3.38"	2 x 11.5	3.3125 x 12	2 x 11.5	39
930003	30	2.4375	15.85	2.88	6.50	YES	4.625"	7.0625"	2.62"	4.00"	---	---	---	15
950005	50	2.375	22.91	3.50	9.63	YES	4.8125"	7.1875"	2.75"	5.00"	---	---	---	24
955019A	50	6.25	69.06	3.75	11.05	YES	11.125"	17.375"	3.13"	5.00"	---	5 x 12	---	51
999000	100	10.25	211.66	5.13	20.65	YES	17.6875"	27.9375"	4.13"	7.00"	---	6.875 x 12	---	160