



PROFESSIONAL LIFTING EQUIPMENT

# WHEN SAFETY DEPENDS ON PERFORMANCE!

## 72850A

### 2,500 Lbs. Capacity Powertrain Lift / Table

#### INTENDED USE

*This lift/table handles powertrain components like engines and their transmissions, engines with transaxle assemblies, rear ends and large electric vehicle batteries. It will also serve as a work table where components can be lowered to a convenient work height for repairs.*



Lowered Position



#### FEATURES

- An air/hydraulic foot pump includes a metered valve for safe lowering of the load.
- Safety overload system in the air/hydraulic pump prevents jack from being used beyond the load-limiting standard.
- Five foot extension hose with quick disconnect fittings stores in the lift base. The foot pump can be removed from its holder and hydraulic hose quickly and easily extended by 5' using the extension hose. This provides hands free operation of the pump anywhere around the lift's perimeter.
- Scissors lift design provides easy 360° access to any component.
- Two heavy duty ratchet tie-downs are included to safely secure the load on the lift table.
- Table top height from 31" to 77-3/4" (with wood saddles) or 27.5" to 74-1/4" (base plate only).
- Four 8" diameter swivel caster wheels for easy maneuverability. Rear wheels can be locked to prevent the lift from rolling.

MODEL NUMBER	CAPACITY @100 P.S.I.	LIFT HEIGHT		OVERALL DIMENSIONS			TABLE SIZE	SADDLE TILT			SHIPPING WEIGHT
		Low	High	Length	Width	Height		Fwd.	Back	Side	
<b>72850A</b>	<b>2,500 lbs.</b>	31"	78"	50"	33"	35"	19" x 36"	15°	15°	±15°	665 lbs.