



PROFESSIONAL LIFTING EQUIPMENT

# WHEN SAFETY DEPENDS ON PERFORMANCE!

72212

## 55 / 37 / 23 / 12 Ton Capacity Air / Hydraulic Telescopic Floor Jack

### INTENDED USE

*Heavy duty truck, rail, bus, agriculture and construction equipment applications.*

### FEATURES

- 50" Long "T" handle helps in positioning jack under vehicles with low overhang.
- Handle locking lever secures handle in either vertical, horizontal or 45 degree position.
- Safety overload system prevents cylinder damage.
- Rust inhibitive coating on rams offers longer life.
- Integrated filter protects air motor.
- Double acting pump raises ram more quickly to the load.
- Suspension loaded axle prevents wheel damage.
- Vacuum operated ram retraction eliminates manual lowering of jack.
- Safety button at the top of the handle can be pushed in to immediately stop the jack operation in case of emergency.
- Includes a removable 2-3/4" diameter saddle, 2-9/16" and 5-7/8" long extensions with extension holder.



MODEL NUMBER	CAPACITY (TONS) @ LIFTING STAGE				LIFT HEIGHT		OVERALL DIMENSIONS		PISTON STROKE	HANDLE LENGTH	P.S.I. RANGE	SHIPPING WEIGHT
	1	2	3	4	Low	High	Length	Width				
72212	55	37	23	12	6"	15.375"	39.25"	8.625"	9.5"	61.75"	100-175	233 lbs.



PROFESSIONAL LIFTING EQUIPMENT

# WHEN SAFETY DEPENDS ON PERFORMANCE!

72218

## 33 / 20 Ton Capacity Air Operated Hydraulic Floor Jack

### INTENDED USE

*Heavy duty truck, rail, bus, agriculture and construction equipment applications.*

### FEATURES

- 50" Long "T" handle helps in positioning jack under vehicles with low overhang.
- Handle locking lever secures handle in either vertical, horizontal or 45 degree position.
- Safety overload system prevents cylinder damage.
- Rust inhibitive coating on rams offers longer life.
- Integrated filter protects air motor.
- Double acting pump raises ram more quickly to the load.
- Suspension loaded axle prevents wheel damage.
- Vacuum operated ram retraction eliminates manual lowering of jack.
- Safety button at the top of the handle can be pushed in to immediately stop the jack operation in case of emergency.
- Includes 2" and 3-15/16" stackable extensions with extension holder.



MODEL NUMBER	CAPACITY (TONS) @ LIFTING STAGE				LIFT HEIGHT		OVERALL DIMENSIONS		PISTON STROKE	HANDLE LENGTH	P.S.I. RANGE	SHIPPING WEIGHT
	1	2	3	4	Low	High	Length	Width				
72218	33	20	--	--	6"	12"	16"	6.75"	6.125"	49.25"	120-175	100 lbs.



PROFESSIONAL LIFTING EQUIPMENT

# WHEN SAFETY DEPENDS ON PERFORMANCE!

72225

## 50 / 25 Ton Capacity Air / Hydraulic Telescopic Floor Jack

### INTENDED USE

*Heavy duty truck, rail, bus, agriculture and construction equipment applications.*

### FEATURES

- 50" Long "T" handle helps in positioning jack under vehicles with low overhang.
- Handle locking lever secures handle in either vertical, horizontal or 45 degree position.
- Safety overload system prevents cylinder damage.
- Rust inhibitive coating on rams offers longer life.
- Integrated filter protects air motor.
- Double acting pump raises ram more quickly to the load.
- Suspension loaded axle prevents wheel damage.
- Vacuum operated ram retraction eliminates manual lowering of jack.
- Safety button at the top of the handle can be pushed in to immediately stop the jack operation in case of emergency.
- Includes a removable 2-3/4" diameter saddle, 2-9/16" and 5-7/8" long extensions with extension holder.



MODEL NUMBER	CAPACITY (TONS) @ LIFTING STAGE				LIFT HEIGHT		OVERALL DIMENSIONS		PISTON STROKE	HANDLE LENGTH	P.S.I. RANGE	SHIPPING WEIGHT
	1	2	3	4	Low	High	Length	Width				
72225	50	25	--	--	8.75"	16.5"	39.25"	8.625"	7.875"	61.75"	120-175	235 lbs.



PROFESSIONAL LIFTING EQUIPMENT

# WHEN SAFETY DEPENDS ON PERFORMANCE!

72244

## 44 Ton Capacity Air Operated Hydraulic Floor Jack

### INTENDED USE

Heavy duty truck, agricultural and heavy construction equipment. Ideal for loaded truck and trailer roadside service calls. Heavy enough for rail and bus work.

### FEATURES

- A double acting pump raises the ram more quickly to the load.
- Suspension loaded axle prevents wheel damage.
- Vacuum-operated ram retraction eliminates manual lowering of jack.
- Safety button at the top of the handle can be pushed in to immediately stop the jack operation in case of emergency.
- Includes a 2-3/4" diameter saddle, 2" and 4" long stackable extensions and extension holder.



MODEL NUMBER	CAPACITY (TONS) @ LIFTING STAGE				LIFT HEIGHT		OVERALL DIMENSIONS		PISTON STROKE	HANDLE LENGTH	P.S.I. RANGE	SHIPPING WEIGHT
	1	2	3	4	Low	High	Length	Width				
72244	44	--	--	--	9.25"	15.625"	21.625"	8.125"	5.5"	61.75"	130-175	149 lbs.