

| MODEL NUMBER | HYDRAULIC PRESSURE RATING (P.S.I.) | USABLE OIL CAP. (Cu. In.) | OUTPUT FLOW RATE (Cu. In. Per Min.) | | AIR PRESSURE RANGE (P.S.I.) | AIR CONSUMPTION (scfm) | VALVE FUNCTION | SOUND LEVEL (dBA) | THREAD CONNECTIONS | | DIMENSIONS (Inches) | | | WEIGHT (Lbs.) |
|----------------|------------------------------------|---------------------------|-------------------------------------|------|-----------------------------|------------------------|---------------------------|-------------------|--------------------|-----------------|---------------------|--------|--------|---------------|
| | | | No Load | Load | | | | | AIR (NPT) | HYDRAULIC (NPT) | Length | Width | Height | |
| 910017B | 10,000 | 127 | 60 | 10 | 25-125 | 12 | Advance / Hold Retract | 76 | .25"-18 | .375"-18 | 13.63" | 6.19" | 8.19" | 14 |
| 910018B | 10,000 | 462 | 60 | 10 | 25-125 | 12 | Advance / Hold Retract | 76 | .25"-18 | .375"-18 | 13.63" | 12" | 11.38" | 38 |
| 910020 | 3,250 | 36 | 40 | 8 | 60-120 | 9 | Advance / Hold Retract | 85 | .25"-18 | .125"-27 | 15.5" | 4.5" | 5" | 9 |
| 910130A | 10,000 | 122 | 80.5 | 12.8 | 40-170 | 24 | Advance / Hold Retract | 85 | .25"-18 | .375"-18 | 12.5" | 5.75" | 8" | 22 |
| 910140 | 10,000 | 462 | 80.5 | 12.8 | 40-170 | 24 | Advance / Hold Retract | 85 | .25"-18 | .375"-18 | 14" | 8.5" | 10.75" | 44 |
| 910165 | 10,000 | 122 | 80.5 | 12.8 | 40-170 | 24 | Advance / Hold Retract | 85 | .25"-18 | .375"-18 | 10.25" | 5.125" | 7" | 17 |