

# WHEN SAFETY DEPENDS ON PERFORMANCE!

### 71233A

## 2 Ton Capacity Double Pump Floor Jack

### INTENDED USE

An economical floor jack designed for a variety of automotive shop uses where strength, speed, and dependability are required.

### **FEATURES**

- Extremely low 2 3/4" low lift height.
- 2 3/4" low and 20" maximum lift heights (without saddle adapter).
- 5 3/4" low and 23" maximum lift heights (with saddle adapter).
- Safety bypass and overload systems prevent cylinder damage and prevent the jack from being used beyond the ASME/PASE load-limiting standard.
- Heavy duty chassis for added strength and dependability.
- 50.25" long two-piece handle for easy shipping and storage.
- Foam handle sleeve is included to protect vehicles from damage.
- Dual pump piston design raises the jack to maximum height in 8-1/2 pump strokes.
- U-joint release mechanism for more control.

Also available is our unique 3" saddle extension adapter (Model #71303). Its Patent Pending design has been created to quickly lift the load. Since most SUV's and Service Trucks have a higher low lift height, the increased height of the saddle allows for quicker positioning and quicker lifting of the vehicle. It saves time and effort and increases shop efficiency.



Model #	Capacity	Lift Height		Overall Dimensions		Handle Length	Woight
		Low	High	Length	Width	Length	Weight
71233A	2 Ton	2.75"	20"	27.875"	14.625"	50.25"	88 lbs.

