norco®

PROFESSIONAL LIFTING EQUIPMENT

WHEN SAFETY DEPENDS ON PERFORMANCE!

76720C

20 Ton Capacity *Low Height* Air Operated Hydraulic Bottle Jack

INTENDED USE

For use in heavy duty trucks, farm equipment, building construction, construction and mining equipment, mobile home set-up and oil field applications.

FEATURES

- Fast efficient air pump reduces lifting time and has a built-in relief mechanism which prevents the jack from being used beyond its maximum allowable capacity.
- Convenient push button air valve connected to an in-line filter prevents contaminates from entering the air/hydraulic system.
- Double spring return.
- Unique design allows for manual operation when air is not available.
- Two piece zinc plated handle.
- Parkerized coating on pump piston, extension screw and extension adapters and chrome coated ram offer protection against rust.
- Longer wear life due to internally machined oil passages, smooth bearing surfaces and close tolerances.
- Safety bypass and overload systems prevent cylinder damage and prevent the jack from being used beyond the ASME/PASE load-limiting standard.
- Carrying handle.

MODEL NUMBER	CAPACITY	LIFT HEIGHT Low	LIFT HEIGHT High	STROKE	SCREW EXTENSION	BASE SIZE	P.S.I. RANGE	SHIPPING WEIGHT
76720C	20 Ton	8.22"	15.27"	4.06"	2.19"	6.56" x 9"	100-130	38 lbs.

365 W. Victoria St. • Compton, CA 90220 • Phone: 310-639-4000 • Toll Free: 800-347-2232 • Fax: 310-639-7411 • *www.norcoindustries.com*