



PROFESSIONAL LIFTING EQUIPMENT

WHEN SAFETY DEPENDS ON PERFORMANCE!

925010B

10,000 P.S.I. Single-Speed Steel Hand Pump

INTENDED USE

For many applications including shop, agricultural, automotive/truck service needs and construction maintenance applications where high pressure pumps are required to activate cylinders rated as high as 55 ton capacity.



FEATURES

- 3/8 NPT hose connection on all pumps.
- Internal pressure relief valves for overload protection.
- External load release valve for single-acting cylinder operation.

PUMP TYPE				MODEL NUMBER	PRESSURE RATING (P.S.I.)		USABLE OIL CAP. (Cu. In.)	OIL DISPLACEMENT PER STROKE (Cu. In.)		MAXIMUM HANDLE EFFORT (Lbs.)	PISTON STROKE (In.)	DIMENSIONS (Inches)			PUMP HANDLE ARC	WEIGHT (Lbs.)
Single Speed	Two Speed	Steel	Light Weight		1st. Stage	2nd. Stage		1st. Stage	2nd. Stage			Length	Width	Height		
●		●		925009A	2,850	—	18	.16	—	57	.81	13.38	5.25	5.25	40°	11
●		●		925010B	10,000	—	40	.16	—	111	.81	23	5.25	5.25	40°	13
	●		●	925011	200	10,000	55	.687	.151	93	1.00	21.63	4.75	7	50°	9
●			●	925012A	10,000	—	55	.151	—	85	1.00	21.63	4.75	7	50°	9
	●	●		925013B	350	10,000	134	.99	.15	104	1.00	22.5	5.75	7	50°	24
	●		●	925014	400	10,000	155	2.40	.151	95	1.00	21.75	4.75	9	50°	22